

PT-E300VP

Handheld Electrician Labelling Printer



Top Features:

Backlit graphic display

- Easy-to-read text and the ability to preview your label before printing.

Multiple power options

- Supplied with an AC adaptor and a rechargeable Li-ion rechargeable battery. Also works with 6 AA batteries (not supplied)

Lots of built-in contents

- Customise labels using a choice of 7 fonts, 9 frames and 384 symbols

Built-in easy access, industrial strength cutter

- Guaranteed to cut strong adhesive tapes
- With cut/pause to help reduce waste

Standard PC style keyboard

- Makes typing efficient.

Convenient labelling

- Handheld design and battery power lets you print labels wherever they are required.

Smart label application keys to save time

- General/Faceplate
- Cable Wrap/Cable Flag/Heat Shrink Tube/¹Self-laminated
- Patch Panel / Punch Down Block
- Serialize / Advanced Serialize

General

	PT-E300VP labelling machine 18mm strong adhesive black on yellow 8m tape cassette
Carton contents	Li-ion rechargeable battery AC adaptor Wrist strap Documentation Carry case
Language support	English, German, French, Spanish, Portuguese, Italian, Dutch, Danish, Norwegian, Swedish, Finnish, Hungarian, Czech, Polish, Romanian, Slovenian, Slovakian, Croatian, Turkish, Brazilian Portuguese

Dimensions & Weights

Without carton	133(w) x 220(d) x 74(h) 740g
With carton	391(w) x 331(d) x 128(h) 2.89kg
Master carton	408(w) x 403(d) x 377(h) 10.01kg
Products per master carton	3

Built In Features

Keyboard	64 Key Rubber QWERTY/QWERTZ/AZERTY
Dedicated number keypad	Yes
Display type	Backlit Graphic Monochrome LCD with label preview capability
Display resolution	15 characters by 3 lines 128 x 56 dots
Printing speed	20mm/second
Print resolution	180dpi
Maximum print height	15.8mm
Cutter type	Manual full cutter (with cut/pause feature) (fluorine-coated to cut strong adhesive tapes)
Label length	25mm minimum 300mm maximum
Maximum lines per label	5 (for 18mm wide tape)
Tape margins	Large Margin, Small Margin, Chain, No Cut
Vertical text printing	Yes
Mirror printing	No
Copies	1 to 50
Automatic numbering	Count 1 to 50 Incremented by 1 to 9 Numeric and Alphanumeric Standard, Simultaneous or Advanced

Label Creation

Smart label application keys	General/Faceplate Cable Wrap/Heat Shrink Tube/ ¹ Self-laminated /Cable Flag, Patch Panel / Punch Down Block
Fonts	7 Helsinki, Brussels, Los Angels, Atlanta, Adams, Sofia, Letter Gothic
Font styles	9 (excl. Normal) Normal, Bold, Outline, Shadow, Solid, Italic, Italic Bold, Italic Outline, Italic Shadow, Italic Solid
Font sizes	6, 9, 12, 18, 24, 36, 42 point
Symbols	384
Frames	7
Barcodes	9 CODE39, ITF 2/5, EAN13, EAN8, UPC-A, UPC-E, CODABAR, GS1-128 (UCC/EAN128), CODE128

Memory

Max. characters per label	200
Label memory locations	50 (or up to 2,400 characters)

Supplies

Tape type	TZe, HGe, HSe (Heat Shrink Tube), ¹ Self-laminated
Tape widths	3.5, 6, 9, 12 and 18mm

Optional Accessories

Batteries	BA-E001 Li-ion rechargeable battery AA alkaline/rechargeable batteries (LR6/HR6)
AC adaptor	AD-E001

¹ From 2014. May require firmware update.